

Features

- 1/3" Color Sony Super HAD II CCD
- 700 TV lines resolution
- 80 IR LEDs (295'/90m range)
- 3.5-16mm or 5-50mm vari-focal
- External lens and OSD controls
- Installer video output
- Concealed bracket
- Weatherproof IP66
- 12VDC/24VAC
- 3-year warranty



Model	B700V3	B700V5
Lens	3.5-16mm	5-50mm
Horizontal Field of View	68.9° - 17.0°	43.0° - 6.1°
Image Sensor	1/3" Interline Transfer Sony Super HAD II CCD	
TV System	NTSC	
Picture Elements (pixels)	976 (H) x 494(V)	
Horizontal Resolution	700 TV Lines	
Min. Illumination	0.01 lux (0 lux with IR On)	
Signal to Noise Ratio	More than 50dB	
Video Output	1Vp-p 75ohm	
IR LEDs	80 LEDs, 850nm (semi-visible)	
LED controls	On/Off - High/Low power	
OSD Options	DNR - 2D-DNR On/Off / WDR - Digital Wide Dynamic On/Off / AGC - Off/Low/Medium/High White Balance - ATW/Manual/AWC / Privacy Zone - On/Off Selectable (8 zones) Sharpness - Level Adjustable	
Power Requirement	12VDC-24VAC ±10%, 1.1A (26W) Max	
Synchronizing System	Internal	
Operating Condition	+14 ~ 122°F (-10°C ~ +50°C) Within 90% RH	
Weight / Color	5.2 lbs. (2.4kg) / Ivory	

Specifications Subject To Change – C0603

