

## Features

- 1/3" Color Enhanced Sharp CCD
- 700 TV lines, 0.02 lux
- Digital Wide Dynamic function
- Smart DNR (Digital Noise Reduction)
- True Day/Night (moving filter)
- Compatible with external IR illuminators with photocell following contacts
- Up-the-coax OSD controller (option)
- 12 - 24VAC/DC
- 3-year warranty



Model	DN700A
Image Sensor	1/3" 960H Enhanced Sharp CCD
TV System	NTSC
Picture Elements (pixels)	976 (H) x 494(V)
Horizontal Resolution	700 TV Lines
Min. Illumination	0.02 lux
Signal to Noise Ratio	More than 50dB
Video Output	1Vp-p 75ohm
Auto-Iris Drive	DC/Video (4-pin square connector)
White Balance	ATW / AWC / Manual
Electronic Iris	1/60-1/100,000 - On/Off Selectable
BLC (Backlight Compensation)	On/Off Selectable (2 zones)
AGC (Automatic Gain Control)	Off, Low, Middle, High Selectable
Digital Wide Dynamic Range (WDR)	On/Off Selectable
OSD Options	<b>Privacy Zone</b> - On/Off Selectable (8 programmable zones) / <b>Mirror Monitor</b> - CRT-LCD-User / <b>DNR</b> - On/Off, Level / <b>Camera Title</b>
Day/Night Function	Color / B&W / Auto / Ext (camera switches to Night mode when triggered by IR lamp photocell)
RS-485 Input	Pelco-D
Power Requirement	12-24VAC/DC ±10%, 250mA Max
Synchronizing System	Internal
Operating Condition	+14 ~ 122°F (-10°C ~ +50°C) Within 85% RH
Lens Mount	CS-Mount with Cam-type Backfocus Adjustment
Dimensions – w/h/d	2.2 x 2.1 x 3.6 inches (90 x 58 x 54mm)
Weight / Color	10.5 oz. (300g) / Ivory

Lens sold separately. Specifications Subject To Change – G0503

